



METRIC  
 Deep, FLANK DRIVE® Flare Nut  
 Crowfoot Wrenches  
 3/8" sq dr  
 11 through 19mm,  
**21 & 24mm**



**Applications include:**


- Power steering and other lines on domestic and import vehicles **18 & 21mm**
- Hydraulic lines on industrial equipment **15, 17, 18 & 19mm**
- Expansion valves & A/C lines on Mercedes **17, 19mm & 24mm**

**Features:**

- Thinwall for for access around obstacles near the line
- Twelve point flare configuration for accessibility
- High grade steel for strength and reliability
- FLANK DRIVE® wrenching configuration

**Specifications, inches (mm)**

Size	Stk. No.	A	B	C	D
11mm	ANM11	0.74 (18.90)	0.30 (7.50)	0.64 (16.30)	0.59 (15.00)
12mm	ANM12	0.74 (18.90)	0.33 (8.30)	0.64 (16.30)	0.59 (15.00)
13mm	ANM13	0.83 (21.20)	0.38 (9.70)	0.70 (17.70)	0.59 (15.00)
14mm	ANM14	0.83 (21.20)	0.41 (10.50)	0.70 (17.70)	0.59 (15.00)
15mm	ANM15	0.97 (24.60)	0.44 (11.30)	0.74 (18.80)	0.75 (19.10)
16mm	ANM16	0.97 (24.60)	0.48 (12.30)	0.74 (18.80)	0.75 (19.10)
17mm	ANM17	1.05 (26.60)	0.51 (13.00)	0.78 (19.70)	0.75 (19.10)
18mm	ANM18	1.14 (29.00)	0.55 (13.90)	0.82 (20.90)	0.78 (19.80)
19mm	ANM19	1.14 (29.00)	0.57 (14.60)	0.82 (20.90)	0.78 (19.80)
21mm	ANM21	1.21 (30.9)	0.59 (14.90)	0.86 (21.90)	0.78 (19.80)
24mm	ANM24	1.39 (35.3)	0.74 (18.7)	0.97 (24.6)	0.81 (20.6)



**WARNING** • Read & follow instructions before use.